

# AFFF Foam Extinguishers

Stored Pressure

## Fire Extinguisher Product Specification

MODEL AFFF	9 ltr	6 ltr	3 ltr	2 ltr
Capacity (litres)	9	6	3	2
Full Weight (kg)	13.25	9.25	6.1	3.7
Height (mm)	610	515	450	380
Cylinder Diameter (mm)	182	162	160	110
Minimum Discharge (s)	45	30	18	6
Temperature Range (°C)	+5 to 60	+5 to 60	+5 to 60	+5 to 60
Working Pressure at 20°C	13.5 bar	13.5 bar	13.5 bar	13.5 bar
Test Pressure	25 bar	25 bar	25 bar	28 bar
Fire Rating	21A:233B	21A:183B	13A:70B	8A:55B
Kitemarked to BS EN3:2009	Yes	Yes	Yes	Yes

**AFFF- Aqueous Film Forming Foam:** Foam spray extinguishers designed for multi risk fire situations where both Class A combustible materials and Class B flammable liquids are likely to be found, or where Class B creates a direct hazard. AFFF exts are especially effective for Class B fires involving flammable liquids such as fats/oils/spirits/some plastics.

AFFF creates a blanket effect when released, smothering the flames thus preventing the re-ignition of fire by sealing the surface of the solution. A very effective fire fighter.

FGM Fire Protection reserve the right to change the design and specification of fire extinguishers without prior notice.

